

- **55%** Savings over petrol Gensets
- Compliant to revised emission norms





KOEL Chhota Chilli Gensets are powered by high-efficiency diesel engines. So you get the double benefit of higher efficiency and lower fuel costs. KOEL Chhota Chilli

Watts of

Cooling

provides full rated power at just 1.5 Litre of Diesel per hour. That means a saving of upto 55% in your fuel costs, as compared to Petrol Gensets.

Don't limit your power back-up to 4 lights + 4 fans.

Include the comforts of running Air-conditioner<sup>+</sup> and Refrigerator<sup>+</sup>. With KOEL Chhota Chilli, you can run

your Air-conditioner and Refrigerator. So whether it's your family or clients, you can ensure their comfort during long hours of power cuts.



Enjoy the benefits of mobility and portability in a Genset. KOEL Chhota Chilli rolls on wheels and is equipped with a trolley handle. Now you carry power with you for a beach party

or a jungle camp. This feature is of great help for small establishments and mobile workshops too!

The revolutionary sound absorption system makes you totally relaxed during power cut. It complies to the Noise Regulation and Emission Norms of Central Pollution



Control Board. In compliance with the new emission norms, KOEL Chhota Chilli also keeps pollution at bay.



KOEL Chhota Chilli Gensets reach you through a well-trained network of authorized dealers and are supported by over 5000 skilled engineers spread across

India. Quality of service and response time is centrally monitored by KOEL. Dial the toll-free number and our authorized representative will be promptly available at your door step!

DIESEL PORTABLE GENSET			3kVA		5kVA	
Genset Model			CC1-3AS#	CC1-3AS1	CC1-5AS#	CC1-5AS2
Prime Rating at rated RPM		kVA	3	3	5	5
Power Factor		Lagging	0.8			
Voltage		V	230, Single Phase (with AVR Technology)			
Governing ( As per ISO 8528 Part-V class )			G2			
Noise Level (1M)		dBA	≤75	≤70	≤75	≤70
Fuel Consumption*	At 100 % Load	Ltrs/hr	1.00	1.00	1.50	1.50
	At 75 % Load		0.75	0.75	1.20	1.20
	At 50 % Load		0.60	0.60	0.90	0.90
Fuel tank capacity		Ltrs.	12.5	13	12.5	13
Overall dimensions of genset <sup>^</sup>	Length	mm	1150	920	1150	970
	Width	mm	560	560	560	580
	Height	mm	840	920	840	970
Weight of genset with canopy ^	Dry	kg	180	180	190	190
	Wet	kg	190	190	200	200
ENGINE						
Engine Model			CC306 G1	CC306 G1	CC418 G1	CC418 G1
Rated output (prime continuous rating as per ISO 3046)		kW	3.38	3.38	5.50	5.50
		HP	4.60	4.60	7.48	7.48
No. of cylinder		Number	1 1			
Cubic capacity		СС	306	306	418	418
Rated Speed		RPM	3000	3000	3000	3000
Cooling System			Air Cooled			
Aspiration		NA/TC/TA	NA			
Lub Oil change period		Hrs.	200			
Lub oil Sump Capacity		Ltrs.	1.1	1.1	1.65	1.65
ALTERNATOR						
Insulation Class			Class H			
Alternator Efficiency at (100 % Load) 0.8 pf **			74%			
Max Voltage Dip at Full Load 0.8 pf Lag			<u>≤</u> 20 %			
Max Time to build up rated voltage at Rated RPM			< 5 sec provided engine reach the rated speed			
BATTERY						
Electrical Battery starting voltage		Volts-DC	12			
Starting System			Electric	Electric/ Recoil Start	Electric	Electric/ Recoil Star

## Typical appliance configuration



^ Tolerances Apply

\* With 0.845 Specific Gravity of diesel ( 5 % Tolerance )

\*\* Efficiency of Alternator as per standards IS 4722 and IEC 34-1

# Genset Model will be available in 4 Wheel configuration

+ Applicable for 5 kVA genset only

Product improvement is a continuous process. Kindly contact KOEL for latest information

• Ahmedabad: 079 - 2692 9687/89 • Bengaluru: 080 - 490 31130 • Bhubaneshwar: 0674 - 258 8047 • Chennai: 044 - 237 44624 • Delhi: 011 - 2871 5826

- Guwahati: 0361 245 7616 Indore: 0731 3913100 Jaipur: 0141 2370007 Kochi: 0484 238 5757 Kolkata: 033 217 0858 Lucknow: 0522 274 1442
- Ludhiana: 0161 254 6668 / 69 Meerut: 0121 240 1199 Mumbai: 022 6151 1234 Patna: 0612 222 0412 Pune: 020 2581 0341

• Secunderabad: 040 - 275 34176 / 97

## KIRLOSKAR OIL ENGINES LIMITED

Laxmanrao Kirloskar Road, Khadki, Pune 411 003 INDIA. www.koelgreen.com



Stamp of Authorised Representative